



Gazpromneft Moto 4T 10W- 30

Four-Stroke Motorcycle Engine Oil



Engine oil



Small 4T engines



Wear protection



Engine cleanliness



Excellent friction performance



Semisynthetic

Gazpromneft Moto 4T 10W-30 is high quality semisynthetic four stroke motorcycle engine oil, designed for use in high performance motorcycle engines operating under a wide variety of conditions, including severe operations. It is formulated with premium quality base oils in combination with shear stable viscosity index (VI) improvers and selected additive package, providing multifunctional oil for engines requiring JASO MA2 and API SL lubricants. Gazpromneft Moto 4T 10W-30 protects against wear and damage even in the stressful conditions of stop-and-go city traffic.

Applications



- Four-stroke motorcycle engines where API SL or JASO MA2 fluids are required
- Motorcycles with or without immersed clutches
- Optimized for lubrication systems where engine, gearbox and clutch are integrated (wet sump)
- Small four-stroke gasoline engines requiring API SL performance (or lower)
- Gardening equipment that specify 10W-30 viscosity grade
- Four stroke outboard/inboard air-cooled engines

Features	Advantages and Potential Benefits
Optimised friction control	Smoother clutch engagement and elimination of clutch slippage for easy gear changes and maximum power transfer
Outstanding thermal and oxidation stability	Oxidation protection at all operating temperatures minimizing deposit formation found in air-cooled engines
Wear protection	Helps to reduce wear in highly stressed engine and gearbox components under severe operating conditions
Effective detergent and dispersant capability	Control deposits formation to prevent sludge and keep your engine clean and running smoothly
Excellent anti-corrosive protection properties	Prolonged useful life of the valve controls and bearing components

Meet the requirements

- API SL

Approvals

- JASO MA2

Typical Characteristics

Properties	Method	Gazpromneft Moto 4T 10W-30
SAE Viscosity Grade	SAE J300	10W-30
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	82,7
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	12,3
Viscosity Index	ASTM D2270	145
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D97	-36
Density @15°C, kg/m ³	ASTM D4052	873
Sulfated Ash, wt%	ASTM D874	1,3

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.