

Gazpromneft Antifreeze SF12+

High Performance Antifreeze

Gazpromneft Antifreeze SF12+ is extra high performance coolant made of ethylene glycol. The Organic Acid Technology (OAT) formula gives outstanding protection against frost, corrosion and overheating for engines of both ferrous and aluminum construction. Gazpromneft Antifreeze SF12+ is free of nitrites, amines, phosphates, silicates and borates. Concentrated antifreeze formula needs to be diluted prior to be used.

Applications

- Car, truck and bus engines of both ferrous and aluminum construction
- Gazpromneft Antifreeze SF12+ Concentrate must be diluted prior to be used as recommended by vehicle manufacturer (see dilution chart)
- For preparation of the coolant it is recommended to use distilled or deionized water. Tap water can be used when not excessively hard

Dilution Chart

Antifreeze concentrate/Water, v/v%	Freeze protection
33/67	-18°C
50/50	-36°C
66/34	-65°C

Approvals

- MAN 324 Typ SNF
- YaMZ

Meets the requirements

- Afnor NF R15-601
- ASTM D3306, D4985
- BS 6580-2010
- MB 325.3
- SAE J1034
- VW (G12+)

Typical Characteristics

Properties	Method	Gazpromneft Antifreeze SF12+
Color	visually	red
Density @20°C, g/cm ³	ASTM D1122	1,105-1,115
Refractive Index @20°C	DIN 51423-2	1,425-1,435
Boiling point (Concentrate), °C	ASTM D1120	160
Boiling point (50% volume solution), °C	ASTM D1120	108
Reserve Alkalinity, ml HCl	ASTM D1121	4,0-5,0
pH (33% volume solution)	ASTM D1287	7,8-8,5
Foaming characteristics (33% volume solution)	ASTM D1881	max.30ml/max.2s
Freezing Point (50% volume solution), °C	ASTM D1177	below -36
Water Content, wt%	ASTM D1123	max.3

Available type and size

Product Name	Type	Available Size
Gazpromneft Antifreeze SF12+	Concentrate (needs to be diluted prior to be used)	1kg, 220kg, 1000kg
Gazpromneft Antifreeze SF12+ 40	Ready to use product that has been premixed with concentrate and water to provide efficient protection down to -36°C	1kg, 5 kg, 10kg, 220kg, 1000kg
Gazpromneft Antifreeze SF12+ 60	Ready to use product that has been premixed with concentrate and water to provide efficient protection down to -50°C	220kg
Gazpromneft Antifreeze SF12+ Premix	Ready to use product that has been premixed with concentrate and water to provide efficient protection down to -16°C	1kg, 5 kg, 10kg, 220kg, 1000kg

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

✔ ISO 9001

✔ ISO 14001

✔ ISO/TS 16949

✔ OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63
www.gazpromneft-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: OilSupport@gazprom-neft.ru 09/2019