

Gazpromneft ATF DX II

Automatic Transmission Fluid



Automatic Transmission Fluid



Mineral



Power steering systems



Optimal friction performance



High wear protection



Seal materials compatibility

Gazpromneft ATF DX II is high quality automatic transmission fluid recommended for older passenger car and commercial automatic transmissions. It is designed to maximize transmission performance, reduce transmission wear, prevent leaks and maintain smooth shifting. Gazpromneft ATF DX II can be used in power steering systems and hydraulic applications where automatic transmission fluid is specified.

Applications



- Passenger and commercial automatic transmissions specifying DEXRON® IID level performance
- Power steering systems and hydraulic applications where automatic transmission fluid is specified

Features	Advantages and Potential Benefits
Good thermal and oxidation stability	Reduced deposits and sludge build-up to keep transmissions clean for efficient operation
Good low temperature performance	Good fluidity at low temperatures providing good cold-start shifting
Good anti-wear properties	Reduced wear and extended life in transmissions
Compatible with all common seal materials	Good leakage control

Meet the requirements

- General Motors DEXRON® IID

Typical Characteristics

Properties	Method	Gazpromneft ATF DX II
Color	visually	red
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	7,1
Brookfield @-40°C, mPa·s	ASTM D2983	38000
Flash Point (COC), °C	ASTM D92	220
Pour Point, °C	ASTM D97	-45
Density @15°C, kg/m ³	ASTM D4052	870

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.